



Filtertechnik

Filtration, Purification &
Separation Solutions

HYDROKIT®
For Diesel

Detect Free Water in Diesel Fuel

FEATURES

- **Easy to Use** – Automatically controls the sample size. Simple evaluation by color comparison.
- **Shelf Life** – For details on shelf life refer to date on box
- **Responds Consistently** – Responds consistently in a wide variety of undyed diesel fuels.
- **Carefully Controlled Quality** – Manufactured to strict quality control specifications.

DESCRIPTION

The HYDROKIT® is an effective “Go, No-Go” field test designed to periodically check for free water, which is removed to ppm levels by properly operating filter/separators, **Aquacon®**, and monitor vessels. Samples are normally taken downstream of the vessel, but they can also be taken at other points in the fuel distribution system.

The HYDROKIT® is designed to indicate free water in excess of 200 ppm by changing the powder contained in the sample tube to a pink color. Other concentrations can be estimated using the other colors on the card. The HYDROKIT® provides better water determination than ASTM D2709 or D4176. The HYDROKIT® is designed for “fail-safe” operation, with false negative readings unlikely. Almost any error in performing the test will indicate the presence of wet fuel. If the sample indicates the presence of excessive water, it is always a good practice to repeat the test on a second sample.



APPLICATIONS

- Diesel Fuel, undyed
- Not for use with Avgas

ORDERING INFORMATION

<u>MODEL NO.</u>	<u>QTY OF TEST TUBES</u>
HKD 25	25

Each model above comes complete with:
sample tubes
wide mouth glass sample jar(s)
needle holder assembly
instruction card
color indicator comparison card

How To Use HYDROKIT®

1
Sample bottle
must be clean.



2
Take sample
downstream of
vessel.




3
Push tube down
into needle holder
in sample.




4
After tube fills,
shake for
15 seconds.
Set upright
to allow powder
to settle.



5 Check powder color at one minute.



6 If color is the same or darker than FAIL, more than 200 ppm of free water is present.



Filtertechnik
Filtration, Purification &
Separation Solutions

**Liquid Filtration
and Separation
Specialists**