

## Series 64

### MULTI STACK FILTER HOUSING

The **64 Series Multi cartridge housing** is designed to accommodate 3, 5, 7, 10 or 15 stacks of filters up to 40" long. The centre positioned, split shell opening style is equipped with a Cast Vee clamp as standard for pressures ranging from FV - 10 bar g. Leg mounted with the split shell opening, this is the ideal choice when using Single Open End plug in style cartridges. The simple to lift off lightweight dome allows full and easy access to the cartridges for rapid changeouts. With the free draining clean chamber, the **64 Series** housings suit processes where cleanliness and ease of operation are essential. Accepting both standard Double Open End and Single Open End cartridges, this leg mounted, free standing housing will suit most applications. Bolted closures are an option available for all models. The **64 Series** will accept the full range of Filtertechnik and industry standard cartridges with nominal lengths of 20, 30 and 40".

#### Product Features

- Split body design allows easy access to cartridges on changeout
- Dished bottom end allows complete drainage of clean chamber, leading to improved system cleanliness
- Adjustable strap legs allow the user to set inlet and outlet heights
- Vee clamp closures use unique 'W' style seal for reliable leak free operation
- High quality cast Vee clamps for safety and security
- Cast compression nut with integral PTFE washer for easy, hand tight cartridge sealing
- Wide range of connection sizes and types available
- Universal cup allows the use of plug in Code 3, Code 8 and Code A) and DOE cartridge styles in the same housing
- PED and ATEX Compliant
- DWI Approved product

#### Features and Benefits

- Large selection of housing sizes available so suitable for a wide range of processes
- Integral vent, clean and dirt drains to aid efficient filter changeout
- Each housing hydrostatically pressure tested
- Internally and externally electropolished as standard
- Each housing etched with a unique serial number for full traceability
- Full housing customisation service available
- Universal cup allows the use of plug in (Code 3 and Code 8) or DOE cartridge styles in the same housing
- DWI Approved product

#### Product Range


Filtertechnik design and manufacture an extensive range of liquid filtration systems, providing one of the widest selections of filtration vessels, depth filters and pleated cartridges available today, ensuring excellent process and filter compatibility. As one of Europe's leading manufacturers of filtration systems, Filtertechnik is able to offer a solution to meet all filtration requirements. Filtertechniks' filters are manufactured in clean room conditions and all products come with detailed Product Validation Guides and Technical Support documentation.



## TECHNICAL DATA

### Maximum Operating Conditions

	6403	6405	6407	6410	6415
Liquid: Vee Clamp:	10 Bar g	10 Bar g	10 Bar g	7 Bar g	7 Bar g
Bolted Closure:	FV / 10 Bar g	FV / 10 Bar g	FV / 10 Bar g	FV / 10 Bar g	FV / 6 Bar g
Gas: Vee Clamp:	7.5 Bar g	4.5 Bar g	4.5 Bar g	2 Bar g	1.5 Bar g
Bolted Closure:	FV / 7.5 Bar g	FV / 4.5 Bar g	FV / 4.5 Bar g	FV / 2 Bar g	FV / 1.5 Bar g
Maximum Temperature:	-10°C / 150°C				



### Materials of Construction

Body:	316L St.Steel
Closure:	Vee Clamp - 304 St.Steel Screw Clamps - Zinc plated carbon steel (Optional Stainless Steel)
Vessel Finish:	Electropolished

### Connections

	6403	6410	6415
Inlet / Outlet	2" BSPM	3" BSPM	4" BSPM
Vent:	1/4" BSPM	1/4" BSPM	1/2" BSPM
Drain:	1/2" BSPM	1/2" BSPM	1" BSPM

### PED Status: Compliant with 2014/68/EU

Fluid Groups:	Liquids Group 1 + 2 Gas Group 2
Marking:	CE
Atex:	Compliant with 2014/34/EU, level CE Ex II 2 GD c X

### Ordering guide

